WINGER® WESWW10-CS LED 5 mm 12 V warm white, typ. 3,200 K, up to 10,000 mcd



Item number	51000121
Type	WESWW10-CS
Brand	WINGER®
Package	5 mm, water clear, 12 V (internal resistor)
Emitted colour	warm white, typ. 3,200 K
Luminous intensity	6,000–10,000 mcd
Viewing angle	30°

The WINGER® WESWW10-CS is a through-hole 12 V LED in the widely used 5 mm standard package with a water-clear lens and an internal series resistor. It emits warm white light with a typical colour temperature of 3,200 K, with a luminous intensity of 6,000–10,000 mcd and a viewing angle of 30°. It may be connected directly to a typ. 12 V DC supply (10–23 V).

Typical uses are signalling and status indication as well as illumination or backlighting, depending on the number and arrangement of the LEDs. The resistance of the internal resistor is not stated in the available sources.

1 Optical and Electrical Characteristics

Parameter	Symbol	Min.	Typ.	Max.	Unit	Condition
Supply voltage [2]	V_S	10 [2]	12 [1]	23	V	DC
Viewing angle (50 % power angle)	2θ½		30		°	V_S = 12 V
Luminous intensity	I_V	6,000 [1]		10,000	mcd	V_S = 12 V
Colour temperature	T_C		3,200		K	V_S = 12 V
Recommended forward current	$I_{F(rec)}$		10	20 [1]	mA	V_S = 12 V
Reverse current	I_R			5 [1]	µA	V_R = 5 V

[1] Value according to the previous datasheet version.
[2] Supply-voltage range 10–23 V DC according to the shop (takes precedence). The previous datasheet version stated min. 3 V, typ. 12 V, max. 23 V and “LED may be connected directly to 3…23 V DC”. The typ. value 12 V is taken from the previous datasheet version and from the shop wording “directly on 12 V”. The resistance of the internal resistor is not stated in the sources and is not invented.
Unless otherwise stated, values at V_S = 12 V, typ. I_F = 10 mA, T_A = 25 °C.
This LED has an internal series resistor and may be connected directly to a DC supply in the rated voltage range. The resistance of that resistor is not stated in the available sources.
Measurement tolerances [1]: supply voltage ±0.1 V; luminous intensity ±15 %; viewing angle ±15 %; wavelength ±2.0 nm.
It is strongly recommended to limit the die temperature to 55 °C [1].


2 Absolute Maximum Ratings

Parameter	Symbol	Rating
Forward current	I_F	20 mA [1]
Peak forward current (duty cycle 1/10, pulse width 10 ms)	I_{FP}	120 mA [1]
Reverse voltage	V_R	5 V [1]
Max. power dissipation	P_D	120 mW [8]
Operating temperature range	T_{OPR}	−30 … +70 °C [1]
Storage temperature range	T_{STG}	−30 … +80 °C [1]
Lead soldering temperature	T_{SOL}	260 °C for max. 5 s, 3 mm from the epoxy base [1]

[1] Value according to the previous datasheet version.
[8] Power dissipation 120 mW according to the shop (takes precedence). The previous datasheet version stated P_D = 100 mW.
Absolute maximum ratings at T_A = 25 °C.

3 Characteristic Curves


Relative spectral emission



Typical curves taken over from the previous datasheet version (read graphically, approximate values) – not binding; the table values apply. Spectrum normalised to its maximum (phosphor peak approx. 581 nm; typical warm-white shape). No $I_V(T_A)$ curve in the previous datasheet version. Radiation characteristic omitted (see WESBL02-CS).

4 Mechanical Data

Parameter	Value
Package	5 mm round, through-hole, water-clear lens
Body diameter	Ø 5.0 mm
Flange diameter	Ø 5.8 mm
Body height (flange to lens tip)	8.7 mm
Height from flange front face to lens tip	7.7 mm
Lead spacing / lead cross-section	2.54 mm / 0.54 mm
Lead length	≥ 25 mm (anode; cathode shorter)
Polarity	long lead = anode (+); short lead and flat on flange = cathode (−)
General tolerance	±0.25 mm [1]



Side view (schematic, not to scale). Long lead = anode, flat on flange = cathode side.

[1] Value according to the previous datasheet version.
Dimensions in mm, taken from the product-page drawing (shop). Lead thickness is the single dimension shown on that drawing (not stated as a square cross-section). The 1.5 mm dimension on the shop drawing marks the stepped lead end, not a shortening of the cathode; the cathode is drawn shorter but is not dimensioned. The previous datasheet version stated body Ø 4.9 mm (front view Ø 5 mm), lead thickness 0.5 mm, lead length MIN 25.0 mm and a cathode difference written “2.0~1.0 mm” (typographically unclear). General tolerance ±0.25 mm according to the previous datasheet version [1].

5 Ordering Information and Packaging

Parameter	Value
Item number	51000121
Type	WESWW10-CS
Packaging	loose in bag
Packaging unit	500 pcs per bag

6 Handling and Application Notes

- This LED has an internal series resistor and may be connected directly to a DC supply in the rated voltage range (typ. 12 V; 10–23 V). Do not exceed the rated supply-voltage range. The resistance of the internal resistor is not stated in the available sources.
- When connecting several of these LEDs in parallel, each already has its own internal resistor; still do not exceed the rated supply-voltage range.
- Do not exceed the absolute maximum ratings, not even briefly; avoid reverse voltage.
- Bend the leads only before soldering and at room temperature, never directly at the body (typ. at least 3 mm [4] from the body). Hold the lead firmly between body and bending point; never use the body as a fulcrum.
- Do not apply mechanical stress to the leads or the lens while the LED is hot (during and directly after soldering). Let it cool down to room temperature first.
- Clean with isopropyl alcohol only if necessary; do not use aggressive solvents. Ultrasonic cleaning only after prior qualification.
- Do not look directly into the LED at short distance for a longer period (glare).
- Protect the LED against current surges and overvoltage; limit the die temperature to 55 °C (strongly recommended) [1].

[1] Value according to the previous datasheet version.
[4] Typical value for this LED type; not individually measured / subject to confirmation.

7 ESD Protection

Parameter	Value
ESD withstand voltage (HBM)	1,000 V [4] (HBM, ANSI/ESDA/JEDEC JS-001)

- LEDs are electrostatic-sensitive devices (ESD). Electrostatic discharge or voltage surges can damage the LED immediately or reduce its service life without visible signs.
- Handle and process only in an ESD protected area (EPA) in accordance with IEC 61340-5-1: grounded work surfaces, equipment and soldering irons, wrist straps or ESD gloves, ESD-safe packaging and transport containers.
- Keep the LEDs in their ESD-safe packaging until processing.

[4] Typical value for this LED type; not individually measured / subject to confirmation.

8 Soldering Instructions

Parameter	Value
Wave soldering	max. 260 °C, max. 5 s, at least 3 mm from the body [4]
Preheating (wave soldering)	max. 100 °C, max. 60 s [4]
Hand soldering	max. 350 °C, max. 3 s, at least 3 mm from the body, once only [4]

- Recommended methods: wave soldering or hand soldering. Through-hole LEDs are not intended for reflow soldering unless explicitly stated.
- Solder only once if possible and keep the specified minimum distance between soldering point and body. Never dip the body into the solder.
- Hand soldering: use a temperature-controlled, grounded soldering iron; do not touch the body with the tip.
- Shorten the leads preferably after soldering and without transferring stress to the body.

[4] Typical value for this LED type; not individually measured / subject to confirmation.

9 Storage

Parameter	Value
Storage temperature	−30 … +80 °C
Recommended storage conditions	≤ 30 °C, ≤ 60 % RH, in original packaging [4]
Shelf life	12 months from delivery in unopened original packaging [4]

- Store in the original packaging in a dry, clean environment free of corrosive gases. Avoid condensation and rapid temperature changes.
- High humidity or sulphur-containing atmospheres can discolour the lead surface and impair solderability; process the LEDs promptly.

[4] Typical value for this LED type; not individually measured / subject to confirmation.

10 Environmental Compliance

Parameter	Value
RoHS (EU) 2011/65/EU incl. (EU) 2015/863	compliant (Directive 2011/65/EU) [3]
REACH (EC) 1907/2006	no SVHC of the candidate list above 0.1 % (w/w) known [4]

Declarations of conformity are available on request.
Dispose of as electronic waste in accordance with local regulations.

[3] RoHS compliance according to the previous datasheet version.
[4] Typical value for this LED type; not individually measured / subject to confirmation.

11 Warranty and Application Limits

- Perform an acceptance inspection on arrival of the goods; return defective items stating the defect and quantity.
- Integration of the LEDs into the application and verification of service life and other qualities in practical use shall be carried out by the user.
- Do not use the LEDs in applications requiring higher reliability and safety where failure or malfunction could endanger life or health. The seller assumes no liability for claims or damages resulting from use contrary to the intended purpose or without written consent.
- The seller assumes no responsibility for damage or defects caused by operation at currents exceeding the absolute maximum ratings; these are not covered by warranty.

Values marked [4] are typical values for this LED type and have not been individually measured for this item; they are subject to confirmation. Please contact us for binding values: info@led1.de · +49 340 8508260.

Winger Electronics GmbH & Co. KG · LED1.de® · Sold only to businesses, public authorities, schools and freelancers. “LED1.de” and “WINGER” are registered trademarks. Status: November 2026 – Subject to technical changes and errors.