Winger Electronics SOLAROX® LED Strip 24V, warm-white






Description

- Flexible IP 65 LED Strip
- Emitting Color: warm-white
- 5m reel
- 60 leds per meter
- Divisible 10cm each
- Self-adhesive

Dimension figure



Unit: mm

Tolerances: ±0.25mm

Absolute Maximum Ratings

Item	Symbol	Absolute Maximum Rating	Unit
Max. Supply Current	Is	1	Α
Power Dissipation	Po	24	W
Operating Temperature	T _{OPR}	-15 ~ +40	°C
Storage Temperature	T _{stg}	-40 ~ +80	°C

Typical Optical/Electrical Characteristics

Item	Symbol	Condition	Min.	Тур.	Max.	Unit
Supply Voltage	V_{F}		-	24	-	V
Supply Current	Is		-	-	1	Α
Power Dissipation	Po	5mts length	-	-	24	W
50% Power Angle			-	120	-	deg
Luminous Intensity	I _V		1500	-	1800	lm
Colour Temperature	Tc		2800	-	3500	K

Warranty

- (1) Perform an acceptance inspection on arrival of the goods. Return the defectives if any stipulating the disqualification and quantity.
- (2) Embedding the strips into the application and the verification of life and other qualities in practical use shall be executed by user.
- (3) Do not use the strips for the applications that require the higher reliability and security and that may endanger life and health by the breakdown and the malfunction. Seller shall not bear any responsibility or liability with respect to any claims and damages caused by user's usage of the strips without following our intended purpose or any written consent.
- (4) Seller shall not bear responsibility for any damages or defects caused by improper operation at the current in excess of the absolute maximum ratings that are not covered by warranty.