

# FLOODLIGHT LED 200 W 4000 K BK

# LEDVANCE FLOODLIGHT LED | LED floodlight luminaires



#### Areas of application

- Replacement for floodlights with halogen lamps
- Car parks and underpasses
- Garages
- Public areas
- Building facades
- Construction areas

#### **Product benefits**

- Energy savings of up to 90 % compared to halogen lamp floodlights
- Optimized weight and size due to compact design
- Very homogenous light

#### **Product features**

- Luminaire efficacy: up to 100 lm/W

Beam angle: 100°Type of protection: IP65



# Product datasheet

#### Technical data

### **Electrical data**

Operating mode	Electronic control gear (EVG)	
Nominal wattage	200.00 W	
Nominal voltage	220240 V	
Mains frequency	50/60 Hz	
Nominal current	0.87 A	


### Photometrical data

Color temperature	4000 К
Luminous flux	20000 lm
Luminous intensity	8911 cd
Light color (designation)	Cool White
Color rendering index Ra	>80

### Light technical data

Beam angle	100.00 °

# **Dimensions & weight**



Length	328.0 mm
Width	362.0 mm
Height	125.0 mm

### Colors & materials

Body material	Aluminum
Product color	Black

# Temperatures & operating conditions

### Product datasheet

Ambient temperature range	-2050 °C

### Lifespan


# **Capabilities**

Dimmable	No
Type of connection	Cable, 3-pole

#### Certificates & standards

Protection class	1	
Type of protection	IP65	
Standards	CE/CB/TÜV SÜD/EAC/ROHS	
Energy efficiency class	A	

### **Light Distribution**



LDC typ polar

### Logistical Data

Product code	Product description	Packaging unit	Dimensions (length	Volume	Gross weight
		(Pieces/Unit)	x width x height)		

### Product datasheet

4058075001190	FLOODLIGHT LED	Shipping carton box	455 mm x 390 mm x	29.63 dm³	7810.00 g
	200 W 4000 K BK	1	167 mm		

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

#### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.