

HIGH BAY LED 120 W 4000 K

LEDVANCE HIGH BAY LED | LED high-bay luminaires



Areas of application

- Replacement for high bay luminaires with mercury vapor or metal halide lamps
- Warehouses
- Logistics halls
- Industry
- Indoor and outdoor
- High ceiling (e.g. in shopping malls, airports, commercial buildings, lobbies)

Product benefits

- High luminous efficacy
- Exclusive LEDVANCE design
- Energy savings of up to 50 % compared to conventional high bay luminaires
- 5 years guarantee
- Optimized weight and size due to compact design

Product features

- Type of protection: IP65
- Lifetime (L70/B50): up to 50,000 h (at 25 °C)



Technical data

Electrical data

Operating mode	Electronic control gear (EVG)	
Nominal wattage	120.00 W	
Nominal voltage	100240 V	
Mains frequency	50/60 Hz	
Nominal current	0.522 A	


Photometrical data

Color temperature	4000 К
Luminous flux	13000 lm
Luminous intensity	7064 cd
Light color (designation)	Cool White
Color rendering index Ra	>80

Light technical data

Beam angle	90.00 °

Dimensions & weight



Diameter	295.0 mm
Height	141.0 mm
Product weight	4100.00 g


Colors & materials

Body material	Aluminum
Product color	Black

Temperatures & operating conditions

Ambient temperature range	-3050 °C	
Lifespan		
Lifespan	50000 h	
Capabilities		
Dimmable	No	
Type of connection	Cable, 3-pole	
Certificates & standards		
Protection class	1	
Type of protection	IP65	
Standards	CE/CB/TÜV SÜD/EAC/ROHS	
Protection class IK (shock resistance)	IK08	
	A++/A+/A	

Light Distribution



LDC typ polar

Equipment / Accessories

- Mounting hook and brackets included

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4058075001039	HIGH BAY LED 120 W 4000 K	Shipping carton box 1	335 mm x 335 mm x 215 mm	24.13 dm³	4665.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

References / Links

For Guarantee see

www.ledvance.com/guarantee

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.