
PANEL LED 625 40 W 4000 K

LEDVANCE PANEL LED 625 | LED panel luminaires



Areas of application

- Direct replacement for luminaires with fluorescent lamps
- Corridors
- Offices
- Conference rooms
- Reception areas
- Foyers
- Elevators
- Suitable for recessed ceiling systems with grid size of 625 x 625 mm

Product benefits

- High luminous efficacy
- Energy savings of up to 50 % compared to conventional luminaires
- Easy and quick installation
- Very homogenous light
- 5 years guarantee
- External driver for extended flexibility (compatible with selected DALI drivers)
- Very slim aluminum housing (only 10.5 mm) and matt white frame

Product features

- Type of protection: IP20
- Aluminum housing, polystyrene diffuser
- Ambient temperature in operation: -10...+45 °C
- Lifetime (L70/B50): up to 50,000 h (at 25 °C)
- Certificates: CE, CB, TUEV SUED



Product datasheet

Technical data

Electrical data

Operating mode	Electronic control gear (EVG)
Nominal wattage	40.00 W
Nominal voltage	220...240 V
Mains frequency	50/60 Hz
Nominal current	0.174 A


Photometrical data

Color temperature	4000 K
Luminous flux	4000 lm
Light color (designation)	Cool White
Color rendering index Ra	>80

Light technical data

Beam angle	120 °
------------	-------

Dimensions & weight



Length	620.0 mm
Width	620.0 mm
Height	10.5 mm

Colors & materials

Body material	Aluminum
Product color	White
Cover material	Polystyrene (PS)

Temperatures & operating conditions

Product datasheet

Ambient temperature range	-10...45 °C
---------------------------	-------------

Lifespan

Lifespan	50000 h
----------	---------


Capabilities

Dimmable	No
Type of connection	Terminal, 2-pin


Certificates & standards

Protection class	II
Type of protection	IP20
Standards	CE/CB/TÜV SÜD/EAC/ROHS
Energy efficiency class	A

Light Distribution



LDC typ polar



LDC typ polar

Equipment / Accessories

- Accessories for suspension available
- Recommended DALI Driver for Panel 30W:OTi DALI 35/220...240/1A0 LT2(4052899919440)
- Recommended DALI driver for Panel 33 W:OTi DALI 35/220...240/1A0 LT2 (4052899919440)
- Recommended DALI driver for Panel 40W:OTi DALI 50/220-240/1A4 LT2 L (4052899028098)

Product datasheet

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4058075000704	PANEL LED 625 40 W 4000 K	Shipping carton box 4	720 mm x 170 mm x 670 mm	82.01 dm ³	17256.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

References / Links

For Guarantee see

▶ www.ledvance.com/guarantee

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.
