

PARATHOM Retrofit CLASSIC BA

LED retrofit lamps



Areas of application

- Perfect for decorative installations
- Domestic applications
- General illumination
- Outdoor applications only in suitable luminaires

Product benefits

- Clear lamps with innovative LED "filament" technology
- Design, dimensions, luminous flux comparable to an incandescent or halogen lamp
- Very low energy consumption
- Extremely long life
- No UV and near-IR radiation in the light beam
- Instant 100 % light, no warm-up time
- Can be easily fitted instead of ordinary light bulbs
- Lower thermal output (compared with the standard reference product)

Product features

- Professional LED lamps for line voltage
- Beam angle: up to 300°
- Not dimmable
- Base: E14
- Mercury-free lamps
- Lifetime: up to 15,000 h




Product family datasheet

Technical data

	Electrical data		Photometrical data			Dimensions & weight	Lifespan			Additional product data
Product description	Nominal wattage	Nominal voltage	Color temper- ature	Color render- ing index Ra	Light color (designation)	Overall length	Nominal lamp life time	Number of switching cycles	Lumen main. fact. at end of nom. life time	Base (standard designation)
PARATHOM Retrofit CLASSIC BA 23 2 W/827 E14 FIL	2.00 W	230 V	2700 K	80	Warm White	120.0 mm	15000 h	100000	0.70	E14

		Capabilities
Product description	Mercury- free	Dimmable
PARATHOM Retrofit CLASSIC BA 23 2 W/827 E14 FIL	Yes	No

Product family datasheet



PARATHOM Retrofit CLASSIC BA 23 2 W/827 E14 FIL

Application advice

For more detailed application information and graphics please see product datasheet.

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4052899941786	PARATHOM Retrofit CLASSIC BA 23 2 W/827 E14 FIL	Shipping carton box 10	190 mm x 80 mm x 138 mm	2.10 dm³	275.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Product family datasheet

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.