

---

## LS/PD MULTI 3 CI | Sensors for light management systems



---

### Areas of application

- Offices
- Corridors
- Classrooms
- Training rooms
- Stairways
- Sanitary areas

---

### Product benefits

- Particularly small construction


---

### Product features

- Ceiling installation sensor with moveable sensor head
- Connection via four-pole screw terminal or modular 4c4p-connector
- Movable sensor head

## Technical data

### Dimensions & weight



### Product line drawing

Length	50.0 mm
Width	50.0 mm
Height	25.0 mm
Product weight	30.00 g
Diameter	50.0 mm

### Colors & materials

Product color	White
---------------	-------

### Temperatures

Ambient temperature range	0...+50 °C
---------------------------	------------

### Capabilities

Maximum installation height	4 m
Detection area	6 m <sup>2</sup>
Detection angle	80 ° <sup>1)</sup>
Type of installation	On-top ceiling mounting/Ceiling integration
Operating range, light sensor	20...600 lx <sup>1)</sup>

<sup>1)</sup> Approximately





## Equipment / Accessories

- Surface mounting in connection with SENSOR KIT
- Suitable for MULTleco, DIM MULTleco, DALI MULTleco control unit
-

## Product datasheet

Suitable for DALI Professional Sensor Coupler

### Download Data

File	
	Brochures Energy saving
	Brochures Scenes
	Declarations of conformity LMS MULTI3 SENSORS
	Installation guide LSPD MULTI 3 CI light and presence sensor for ceiling installation

### Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (height x width x length)	Volume	Gross weight
4008321916648		Shipping carton box 10	204 mm x 188 mm x 245 mm	9.40 dm <sup>3</sup>	961.40 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.